



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
EERMU-150 SS R-600a 230V 50Hz 1N

19048291

30/04/2021

DENOMINATION:

Refrigerated wall displays ERMU series (exterior in stainless steel), height 800 mm with 1 door.

DESCRIPTION :

Refrigerated wall displays ERMU SERIES (exterior in stainless steel): HEIGHT 800 mm

- Sanitary epoxy coated galvanised steel inside.
- Two outside finish options: either satin stainless steel (Inox version) or black plastic covered galvanised steel (black version).
- 40 kg/m³ injected polyurethane insulation.
- Copper piping and aluminium flaps evaporator.
- Hermetically sealed copper serpentine ventilated compressor.
- Double glazed doors with anti-mist protection (low E) with inner air chamber and handle.
- Digital display for electronic control of temperature.
- ON/OFF power switch.
- Top horizontal lightning.
- Working temperature: +2 °C, +8 °C (room temperature: 32 °C).

STANDARD OPTIONS :

- Locks

DIMENSIONS



X Width	625 mm	X Gross width	670 mm
Y Depth	565 mm	Y Gross depth	615 mm
Z Height	800 mm	Z Gross height	955 mm
Net Weight	51,0 kg	Gross Weight	53,0 kg
Net volume	0,282 m ³	Gross volume	0,394 m ³

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,156 kW
Amperage (A)	0,92A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,167 kW
Climate class	4
Cooling gas load	28,000 g

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 4 A
--------------------------	---------------

OTHERS

Number of doors	1
Condensation system	Vent.



Catalogue
FOOD SERVICE

Capítulo
REFRIGERATION

Modelo
EERMU-150 SS R-600a 230V 50Hz 1N

19048291

30/04/2021

